

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application. Please cancel claims 7 and 8 without prejudice and amend claims 1, 3 and 13 as follows:

**LISTING OF CLAIMS:**

1. (Currently Amended) An optical fiber holding device, comprising:
  - an optical fiber having a grating;
  - a strip-shaped member, having a rectilinear groove in which the optical fiber is accommodated, a gap formed between a wall surface of the rectilinear groove and the optical fiber, and a gel substance, which remains soft, contacting with the optical fiber and filled in the gap; and
  - a substrate on which the optical fiber and the strip-shaped member are mounted, wherein a positioning mark is provided on the substrate, which is used for positioning the strip-shaped member on the substrate.
2. (Original) An optical fiber holding device according to claim 1, wherein the optical fiber is not contacted with a wall surface of the groove of the strip-shaped member.
3. (Currently Amended) An optical fiber holding device, comprising:
  - an optical fiber having a grating;
  - a heater for heating the grating to a predetermined temperature distribution;

a strip-shaped member, having a rectilinear groove in which the optical fiber is accommodated, a gap formed between a wall surface of the rectilinear groove and the optical fiber, and a gel substance, which remains soft, contacting with the optical fiber and filled in the gap; and

a substrate on which the heater and the strip-shaped member are mounted,  
wherein a positioning mark is provided on the substrate, which is used for positioning the strip-shaped member on the substrate.

4. (Original) An optical fiber holding device according to claim 3, wherein the optical fiber is not contacted with a wall surface of the groove of the strip-shaped member.

5. (Original) An optical fiber holding device according to claim 3, wherein the optical fiber is contacted with the heater.

6. (Previously Presented) An optical fiber holding device according to claim 3, further comprising:

a Peltier element for keeping a temperature level of the predetermined temperature distribution of the grating at a predetermined level; and

a temperature sensor for detecting the temperature of the optical fiber used to control the Peltier element.

7. (Canceled)

8. (Canceled)

9. (Original) An optical fiber holding device according to claim 1, wherein the gel substance includes a silicon compound.

10. (Original) An optical fiber holding device according to claim 3, wherein the gel substance includes a silicon compound.

11. (Original) An optical fiber holding device according to claim 1, wherein the strip-shaped member is made of quartz.

12. (Original) An optical fiber holding device according to claim 3, wherein the strip-shaped member is made of quartz.

13. (Currently Amended) An optical dispersion-equalizer, comprising:  
an optical fiber having a grating;  
a heater for heating the grating to a predetermined temperature distribution;  
a heater control circuit for controlling a temperature of the heater;  
a strip-shaped member, having a rectilinear groove in which the optical fiber is accommodated, a gap formed between a wall surface of the rectilinear groove and the optical fiber, and a gel substance, which remains soft, contacting with the optical fiber and filled in the gap;

a substrate on which the heater and the strip-shaped member are mounted,  
wherein a positioning mark is provided on the substrate, which is used for positioning  
the strip-shaped member on the substrate;

a Peltier element for keeping temperature level of the predetermined  
temperature distribution of the grating at a predetermined level;

a temperature sensor for detecting the temperature of the optical fiber;

a Peltier element control circuit for controlling the peltier element based on the  
temperature of the optical fiber detected by the temperature sensor; and

an optical circuitry for inputting an optical signal to the grating and for  
outputting the optical signal reflected on the grating.

14. (Previously Presented) A method of manufacturing an optical fiber  
holding device comprising an optical fiber having a grating; a heater for heating the  
grating to a predetermined temperature distribution; a strip-shaped member, having  
a rectilinear groove in which the optical fiber is accommodated, and a gel substance  
contacting with the optical fiber is filled; and a substrate on which the heater and the  
strip-shaped member are mounted, said method comprising the steps of

filling the gel substance in the groove of the strip-shaped member;

accommodating the optical fiber in the groove of the strip-shaped member in  
which the gel substance is filled;

mounting the strip-shaped member, in which the gel substance is filled and  
the optical fiber is accommodated, on the substrate on which the heater is mounted;  
and

moving the strip-shaped member on the substrate so as to carry out a positioning of the groove with respect to the heater.

15. (Previously Presented) A method of manufacturing an optical fiber holding device comprising an optical fiber having a grating; a heater for heating the grating to a predetermined temperature distribution; a strip-shaped member, having a rectilinear groove in which the optical fiber is accommodated, and a gel substance contacting with the optical fiber is filled; and a substrate on which the heater and the strip-shaped member are mounted; said method comprising the steps of

securing the strip-shaped member on the substrate on which the heater is mounted;

filling the gel substance in the groove of the strip-shaped member secured on the substrate;

inserting and accommodating the optical fiber in the groove of the strip-shaped member in which the gel substance is filled; and

moving the optical fiber on the heater so as to carry out a positioning of the grating with respect to the heater.

16. (Previously Presented) A method of manufacturing an optical fiber holding device comprising an optical fiber having a grating; a heater for heating the grating to a predetermined temperature distribution; a strip-shaped member, having a rectilinear groove in which the optical fiber is accommodated, and a gel substance is filled; and a substrate on which the heater and the strip-shaped member are mounted, said method comprising the steps of

mounting the optical fiber on the heater which is mounted on the substrate;

coating the optical fiber mounted on the heater with a gel substance;

mounting the strip-shaped member on the substrate and accommodating the

- optical fiber in the groove of the strip-shaped member; and

- moving the strip-shaped member on the substrate so as to carry out a positioning of the grating with respect to the heater.